

Safety Tip of the Week

Your Safety Is Our Business®

Volume 3 – Issue 31 July 31st, 2016

Power Tool Safety

Failing to properly use and maintain electricpowered tools causes thousands of cuts, punctures, pinches, amputations, and electrocutions each year. Tools can seriously injure or kill the user if not properly maintained or used.

Before you use a tool:

- Verify that it bears an electrical test label to indicate it successfully passed inspection and tests for electrical safety within the previous six months.
- Know the application, limitation, and potential hazards of the tool. Operate according to the manufacturer's instructions.
- Inspect the cord for the proper type. Electric-powered tools must either have a three-wire cord with ground or be double insulated. Never use a plug that has its ground prong removed.
- Inspect the tool for frayed cords, lose or broken switches, and other obvious problems. Tools that fail this inspection must not be used. These must be removed from service and labeled "Do Not Use" until repairs are made.

When using the tool:

- Do not use electric-powered tools in damp or wet locations.
- Keep guards in place, in working order, and properly adjusted. Safety guards must never be removed when the tool is being used
- Avoid accidental starting. Do not hold a finger on the switch button while carrying a pluggedin tool.
- Safety switches must be kept in working order and must not be modified. If you feel it necessary to modify a safety switch for a job you're doing, use another tool.
- Work areas should have adequate lighting and be free of clutter.
- Observers should remain a safe distance away from the work area.
- Be sure to keep good footing and maintain good balance.
- Do not wear loose clothing, ties, or jewelry when operating tools.
- Wear appropriate gloves and footwear while using tools.

Don't be a fool...inspect your tools!!

